


ANALOG TO DIGITAL AND DIGITAL TO ANALOG CONVERTER

MODEL - ADCDAC100

This trainer has been designed with a view to provide practical and experimental knowledge of Analog to Digital and Digital to Analog Converter.



SPECIFICATIONS

:

÷

÷

:

:

1. Power supply requirement

- 230V AC, 50 Hz.
- 2. Built in IC based regulated Power supply : +15V to -15 V DC/200 mA.
- Following parts provided on Single PCB with connecting terminals. Analog to Digital converter. - IC ADC0800 - 1 No.
- Digital to Analog converter. IC DAC0800 1 No.
- 4. Built in Audio Signal generator for digital conversion of audio signal: 1KHz
- 5. Logic output Indicators
- 6. High /Low switches
- 7. Active Low Pass Filter Cut off Frequency
- 8. Standard Accessories

- 8 LEDs provided for output level indication.
- 8 Nos provided to apply 0 and 1 level
- 3.4 KHz.
- User Manual with practical and circuit diagrams. Connecting patch cords

EXPERIMENTS

- 1. To carry out Analog to Digital conversion process of analog signal.
- 2. To carry out Digital to Analog conversion process of digital signal.

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.