



FM COMMUNICATION TRAINER

MODEL - FMCOM100

This trainer has been designed with a view to provide practical & experimental knowledge of a general circuit of FM Communication on a SINGLE P.C.B.



SPECIFICATIONS

1. Sine wave generator : with amplitude adjustable from 0-4 Vpp
with frequency adjustable from 0.1 to 10KHz
2. VCO1 : Output signal sine
Input : Modulating signal
Frequency 400KHz to 1500 KHz Amplitude adjustable from 0 -2 Vpp
3. VCO2 : Output signal sine
input : Modulating signal or Marker
Frequency switching on two ranges : 400 KHz to 500 KHz and 500 KHz to 1500 KHz adjustable amplitude from 0 -2 Vpp
4. RF Detector, Balance modulator with adjustable carrier null, ceramic filter, LPF, PLL Detector.
5. Power : 230V, 50Hz
6. Test points
7. Accessories : 1. A Training Manual.

EXPERIMENTS

1. To Generate FM Signal Using FM Modulator
2. To Demodulate FM Signal Using Phase Lock Loop (PLL) Detector

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

Sigma Trainers and Kits
E-113, Jai Ambe Nagar,
Near Udgam School,
Thaltej,
AHMEDABAD - 380054.
INDIA.

Phone(O): +91-79-26852427/ 26850829
Phone(F): +91-79-26767512/ 26767648
Fax : +91-79-26840290/ 26840290
Mobile : +91-9824001168
Email : sales@sigmatrainers.com
: sigmatrainers@sify.com
Web : www.sigmatrainers.com

Dealer:-