



# CHARACTERISTICS OF SUS

MODEL - THY15

This trainer has been designed with a view to provide practical & experimental knowledge of Silicon Unilateral Switch (SUS).



## SPECIFICATIONS

1. Power supply requirement : 230V AC, 50 Hz.
2. Built in Regulated Power supply : 0-5V DC/100 mA continuously variable.  
+24V DC/100 mA.
3. Following parts provided on Single PCB with connecting terminals.  
Silicon Unilateral Switch (SUS) 2N4987 - 1no.
4. All parts are soldered on single PCB of size 8" x 7" with complete circuit diagram screen-printed.
5. Standard Accessories :
  1. User Manual with practical and circuit diagrams.
  2. Connecting patch cords

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

**Sigma Trainers and Kits**  
E-113, Jai Ambe Nagar,  
Near Udgam School,  
Thaltej,  
AHMEDABAD - 380054.  
INDIA.

**Phone(O): +91-79-26852427/ 26850829**  
**Phone(F): +91-79-26767512/ 26767648**  
**Fax : +91-79-26840290/ 26840290**  
**Mobile : +91-9824001168**  
**Email : sales@sigmatrainers.com**  
**: sigmatrainers@sify.com**  
**Web : www.sigmatrainers.com**

**Dealer:-**