TUNED RF AMPLIFIER USING FET

MODEL - AMP26F

This board has been designed with a view to provide practical &s experimental knowledge of Single tuned R.F. Amplifier.



SPECIFICATIONS

1. The complete circuit is printed on a single P.C.B.

SIGMA

- 2. All parts are soldered on single pin tag for easy replacement.
- 3. Explanation, Observation, Alignment and adjustment of Internal and external controls is possible due to Single P.C.B.
- 4. Easy identification of different parts is possible at a glance.
- 5. Easy measurement of voltages and observation of waveforms at any point. Test Points are provided on P.C.B.
- 6. A manual having practical detail is provided with the board.
- 7. Built-in Power supply: +6V DC at 200mA IC Regulated & short circuit protected.
- 8. Field effect transistor(FET) BFW11 1 No
- 9. Power requirement : 230V, 50Hz AC.
- 10. Standard Accessories : 1. A manual having practical details.

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

Sigma Trainers E-103, Jai Ambe Nagar, Near Udgam School, Thaltej, AHMEDABAD - 380054.	Fax ISDN	: 079-26852427 / 26767512 : 079-26840290 / 26759661 : 079-26859162 / 26853758 : sales@sigmatrainers.com : sigmatrainers@sify.com : www.sigmatrainers.com	Dealer:-
---	-------------	---	----------