

CHARACTERISTICS OF ZENER DIODE

MODEL DO2

This trainer has been designed with a view to provide practical and experimental knowledge of Zener Diode.

1		4		. 6	4.1	8
			-	-	- 11	
11	1				100	2.
				21	31	10
	-			21	1.	1
÷	- 6	-8		-		
			1	and and	-	12
			1.4	0	1 190	6 1
	-	-	in the second	0	1.100	. 1

SPECIFICATIONS

- 1. Power supply requirement : 230V AC, 50 Hz.
 - Built in IC based regulated Power supply : 0-20 V DC/100mA continuously variable.
- 3. Following parts provided on Single PCB with connecting terminals.

Zener Diode 5.1 Volt

2.

- Zener Diode 8.2 Volt
- 4. All parts are soldered on single PCB of size 8" x 7" with complete circuit diagram screen-printed.

:

5. Standard Accessories

- 1. A Training Manual.
 - 2. Connecting Patch cords.

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

	Phone(O): +91-79-26852427/ 26850829 Phone(F): +91-79-26767512/ 26767648 Fax : +91-79-26840290/ 26840290 Mobile : +91-9824001168 Email : sales@sigmatrainers.com : sigmatrainers@sify.com
INDIA.	Web : www.sigmatrainers.com