



PULSE AMPLITUDE DEMODULATION TRAINER

MODEL- COM106A-2

This trainer has been designed with a view to provide practical & experimental knowledge of Pulse Amplitude Demodulation on a SINGLE P.C.B.



SPECIFICATIONS

- | | | |
|------------------------------------|---|-----------------------|
| 1. Power supply requirement | : | 230V AC, 50 Hz. |
| 2. Built in IC based power supply. | | |
| 3. Demodulator Sections | : | Low Pass Filter |
| 4. Standard Accessories | : | 1. A Training Manual. |

EXPERIMENTS

1. To study theory of Pulse Amplitude Demodulation.
2. To demodulate PAM signal

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

Sigma Trainers and Kits
E-113, Jai Ambe Nagar,
Near Udgam School,
Thaltej,
AHMEDABAD - 380054.
INDIA.

Phone(O): +91-79-26852427/ 26850829
Phone(F): +91-79-26767512/ 26767648
Fax : +91-79-26840290/ 26840290
Mobile : +91-9824001168
Email : sales@sigmatrainers.com
: sigmatrainers@sify.com
Web : www.sigmatrainers.com

Dealer:-